

SM6500DFi



SILENT INVERTER GENERATOR



FEATURES

- ◆ Quiet - 60 dBA
- ◆ Light - 58 kgs
- ◆ Compact - 638×499×543mm
- ◆ Long Run Time @50 %Load: 9.5 Hours
- ◆ Eco Throttle - More Efficient
- ◆ Starting Method - Push Button or Remote Start
- ◆ Safe Clean Power - Power Sensitive Electronics
- ◆ Stronger Together - Parallel for Double Power
- ◆ 50/60Hz - Versatile for Powering Worldwide Electronics
- ◆ Dual Fuel: Powered by Either Gasoline or LPG
- ◆ Built-in Mobility Kit with Telescopic Handle

TECHNICAL DATA

| | |
|-----------------------------|-------------------------------|
| MODEL | SM6500DFi |
| Max Starting Power | 6500W Gasoline/6000W LPG |
| Running Power | 5500W Gasoline/5000W LPG |
| AC Load (Volts) | 120/240 |
| Phase, Frequency | Single, 60Hz |
| Rated Amperage | 23/46(Gasoline) / 21/42 (LPG) |
| Starting Method | Manual/E-Start/Remote |
| Engine Type | Gasoline |
| Engine Model/CC/Hp | SV320B/322cc/9.5Hp |
| Noise Level | 60dB |
| Fuel Tank Capacity | 13.5L |
| Run Time-50 %Load | 9.5Hrs |
| Run Time-100 %Load | 5.5Hrs |
| Fuel Consumption (50 %Load) | 1.4L/Hr |
| Engine Oil Capacity | 0.7L |
| Digital Display | 9-in-1 LED Meter |
| Circuit Breaker | 1x20A, 1x30A, 1x50A |
| Remote Control | ✓ |
| Eco-Throttle | ✓ |
| Parallel Port | ✓ |
| Socket | 1x20A, 1x30A, 1x50A |
| DC Port | ✓ |
| THD | <%3 |
| Battery | 5AH |
| Wheel | 7 inch |
| Plug | 1x20A, 1x30A, 1x50A |
| Net Weight | 58Kg |
| Gross Weight | 65Kg |
| Packing Dimension(LxWxH) | 715x665x610mm |
| Prodcut Dimension(LxWxH) | 638x499x543mm |
| Q'ty (20GP/40HQ) | 96/264 |

