



Technical Data Sheet

150 Micron Cloth Duct Tape with Rubber Resin Adhesive

Product Description:

A versatile and durable cloth duct tape designed for general purpose sealing, bundling, and reinforcement applications. Constructed with a polyethylene-coated cloth backing and coated with a high-tack rubber resin adhesive. Offers excellent conformability, hand-tearability, and adhesion to irregular surfaces.

Product Construction:

Component	Description
Adhesive Type	Rubber Resin
Backing	Polyethylene-Coated Cloth
Total Thickness	150 micron \pm 10%

Key Features:

- High adhesion to rough and smooth surfaces
- Good conformability and hand-tearable
- Moisture and abrasion resistant
- Suitable for indoor and outdoor use
- Easy to unwind and apply

Typical Performance Values:

Property	Value	Test Method
Peel Adhesion (SS, 180°)	\geq 800 g/inch	ASTM D3330
Tensile Strength	\geq 30 N/cm	ASTM D3759
Elongation at Break	10 – 20%	ASTM D3759
Temperature Resistance	Up to 60°C	Internal Method
Holding Power	\geq 1 hour (1kg @ 25°C)	PSTC-7

Applications:

- General purpose sealing and packaging
- Temporary holding and masking
- Book binding and spine reinforcement
- HVAC duct sealing
- Wire bundling and color coding



Shelf Life & Storage:

12 months from the date of manufacture when stored at 20–25°C, 40–60% RH in original packaging.

Note:

The values presented above are typical and should not be used for specification purposes. Product performance should be tested under actual application conditions.

ZenCorp Tapes - Pack with Confidence

Email: sales@zencorporation.in

Website: www.zencorporation.in

Address: No.1, CH-6, 7th A Cross, AGS Layout, Arehalli, Uttrahalli,
Near Nandini booth, Bengaluru - 560061