



Green PET Masking Tape with Silicone Adhesive (No Liner)

Technical Data Sheet

Product Description:

High-performance polyester (PET) masking tape coated with silicone adhesive. Designed for high-temperature masking applications such as powder coating, anodizing, and plating. The linerless construction ensures ease of use in continuous and automated processes.

Technical Properties:

Property	Specification
Backing Material	PET Film
Color	Green
Adhesive Type	Silicone
Total Thickness	80 ± 5 microns
Adhesion to Steel	≥ 7 N/25mm
Tensile Strength	≥ 100 N/25mm
Elongation at Break	≥ 50%
Temperature Resistance	Up to 200°C (30 mins)
Release Liner	No Liner
Storage Condition	22°C & 50% RH in original packing
Shelf Life	12 months from DOM

Features & Benefits:

- Excellent high-temperature resistance
- Residue-free removal after exposure to heat
- Excellent conformability and tear resistance
- Suitable for powder coating, masking, and splicing applications
- Easy handling due to no liner design

Applications:

- Masking during powder coating and anodizing
- PCB masking in electronics
- Splicing applications in high-temp environments
- Surface protection in critical industrial processes

Available Sizes:

- Width: 3mm to 1000mm
- Length: 33M / 50M standard rolls (custom sizes available)



ZenCorp Tapes - Pack with Confidence

Email: sales@zencorporation.in

Website: www.zencorporation.in

Address: No.1, CH-6, 7th A Cross, AGS Layout, Arehalli, Uttrahalli,
Near Nandini booth, Bengaluru - 560061