



# XpreciaPrime™

Coagulation analyzer for fast and reliable PT/INR testing



- 1 Test strip eject button
- 2 Touchscreen display
- 3 Power button
- 4 Barcode scanner
- 5 Test strip port
- 6 USB port



### Accurate

- Correlation of results with laboratory analysis
- Reliable results, less repetition
- Automatic strip quality check



### Portable

- Available anytime, anywhere
- Ergonomic design - fits in the palm of your hand
- WiFi and wired connection
- Rechargeable battery cell



### Safe to use

- Eject button for safe handling
- PPID – Positive Patient Identification
- Operator ID entry with lockout features



### Easy, intuitive

- Results in less than one minute
- User friendly software and touchscreen
- Automatic calibration - no reagents needed

# Xprecia Prime™

Coagulation analyzer for fast and reliable PT/INR testing

## Technical Specifications

Sample	
Sample type	Finger prick of blood / venous blood*
Sample volume	8 µL
Haematocrit range	25 – 55% inclusive
Reporting range	0.8 – 8.0 INR
Results displayed	'International Normalized Ratio' (INR) and PT in seconds

Features	
Automatic power off	Configurable: disabled, 5 mins, 15 mins, 30 mins
Dimensions	147 × 84 × 32 mm (5.79 × 3.31 × 1.26 in)
Weight	210 g (7.41 oz)
Memory recall	1000 patient results
Design lifetime	3 years or 8,760 tests

Meter operating conditions	
Temperature	15°C – 32°C (59°F – 89°F)
Relative humidity	< 80% (without condensation)
Altitude	Electrical safety tested up to 2000 m

Transport and storage conditions (in packaging)	
Temperature	-20°C – 40°C (-4°F – 104°F)
Relative humidity	< 75% (without condensation)
Altitude	Electrical safety tested up to 2000 m

Test strips storage conditions	
Temperature	2°C – 30°C (35.6°F – 86°F)
Relative humidity	< 75% (without condensation)

\* coming soon

LQC kit storage conditions	
Temperature	2°C – 8°C (35.6°F – 46.4°F)

Power supply	
Model	GTM46161-165.0-USB
Input	100 – 240 V~, 50 – 60 Hz, 0.45 A Mains supply voltage fluctuation +/-10%
Rating	5V === 3.2A
Operating altitude	up to 5000 m
Operating humidity	0 – 93%
Operating air pressure	54 – 1060 hPa
Operating temperature	0°C – 40°C (32°F – 104°F)

Connectivity	
USB	Micro USB
WiFi	802.11b/g/n Note: The WiFi network must be secure
Interface wireless	(2.4GHz)

PC requirements	
Hardware	WiFi adapter (for WiFi connection) Note: Device must be connected to the same wireless network as the analyzer. Spare USB port (for USB connection)
Software	Web browser Note: Internet Explorer is not supported

General	
Input	5V === 0.9A
Rating	3.7V === 0.5A MAX
Capacity	Rechargeable 1.85Ah (LI-ION) with power monitoring
Water ingress rating	IPX0
Pollution degree rating	Pollution degree II
Overvoltage category	Category I