

XpreciaPrime™ 4U

Coagulation analyzer for easy self-monitoring
anytime, anywhere

Technical specifications

Analyzer features

- 1 Test strip eject button
- 2 Touchscreen display
- 3 Power button
- 4 Barcode scanner
- 5 Test strip port
- 6 USB port



Affordable

- Avoid travel expenses and test whenever convenient
- Take control of your health without worrying about your budget



Accurate

- Correlation of results with laboratory analysis
- Reliable results, less repetition
- Automatic strip quality check



Easy, intuitive

- User friendly software and touchscreen
- Automatic calibration - no reagents needed



Rapid results

- Results obtained in under a minute
- No more waiting for lab results



Portable

- Fits easily in your hand
- Micro-USB connectivity
- Rechargeable battery



Safe to use

- Eject button for safe handling

Note: This product is not currently available for sale in the USA

Technical Specifications

Sample			
Sample type	Droplet of blood, note, no lancing device is supplied with this product	Haematocrit range	25 – 55% inclusive
Sample volume	8 µL	Reporting range	0.8 – 8.0 INR
Results displayed	'International Normalized Ratio' (INR) and 'prothrombin time' (PT) in seconds		
Features			
Automatic power off	Configurable: disabled, 5 mins, 15 mins, 30 mins	Weight	210 g (7.41 oz)
Dimensions	147 × 84 × 32 mm (5.79 × 3.31 × 1.26 in)	Memory recall	1000 test results
Design lifetime	3 years		
Analyzer/system operating conditions			
Temperature	15°C – 32°C (59°F – 89°F)	Relative humidity	< 80% (without condensation)
Altitude	Electrical safety tested up to 2000 m		
Transport and storage conditions (in packaging)			
Temperature	-20°C – 40°C (-4°F – 104°F)	Relative humidity	< 75% (without condensation)
Altitude	Electrical safety tested up to 2000 m		
Test strips storage conditions			
Temperature	2°C – 30°C (35.6°F – 86°F)	Relative humidity	< 75% (without condensation)
Supplied accessories			
1 x	Xprecia Prime™ 4U analyzer	1 x	Charger
1 x	Replacement cap	1 x	Power supply (including USB cable and 4 sockets)
1 x	User guide	1 x	Quick start guide
General			
Input	5V --- 0.9A	Rating	3.7V --- 0.5A MAX
Capacity	Rechargeable 1.85Ah (LI-ION) with power monitoring	Water ingress rating	IPX0
Pollution degree rating	Pollution degree II	Overvoltage category	Category I
Connectivity	Micro-USB		

Xprecia Prime™ and all related names, logos, product and service names, designs, and slogans are trademarks of Universal Biosensors Pty Ltd and may not be used without the prior written permission of Universal Biosensors Pty Ltd. All other names, logos, product and service names, designs, and slogans are the property of their respective owners.

Note: This product is not currently available for sale in the USA.



TF - 08, Third Floor, SS Omnia,
Sector 86, Gurgaon 122004

Tel: + +91 9953553369
Email: sales@pocb.co.in
Web: <https://www.pocb.in/primepst>