

BLANK PAGE



IS: 2720 (Part 1) - 1983

(Reaffirmed 2006)

Indian Standard

METHODS OF TEST FOR SOILS

PART 1 PREPARATION OF DRY SOIL SAMPLES FOR VARIOUS TESTS

(Second Revision)

UDC 624:131:37



489998/4

@ Copyright 1984

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHODS OF TEST FOR SOILS

PART 1 PREPARATION OF DRY SOIL SAMPLES FOR VARIOUS TESTS

(Second Revision)

Soil Engineering and Rock Mechanics Sectional Committee, BDC 23

Chairman

DR JAGDISH NARAIN

Members

SRRI P. D. AGARWAL

SHRI B. L. DHAWAN (Alternate) PROF ALAM SINGH SHRI B. ANJIAH

SHRI E. M. BENJAMIN
SHRI N. C. DUGGAL (Alternate)
CHIEF ENGINEER (IPRI)

DIRECTOR (DAM) (Alternate)
SHRI A. G. DASTIDAR

DR G. S. DHILLON DIRECTOR

DEPUTY DIRECTOR (Alternate)
DIRECTOR, IRI

SHRI A. H. DIVANJI

SHRI A. N. JANGLE (Alternate)
DR GOPAL RANJAN

SHRI S. GUPTA (Alternate)

Representing

Association of Indian Universities, New Delhi

Public Works Department, Government of Uttar Pradesh, Lucknow

University of Jodhpur, Jodhpur Engineering Research Laboratories, Government of Andhra Pradesh, Hyderabad Concrete Association of India, Bombay

Irrigation Department, Government of Punjab, Chandigarh

In personal capacity (5 Hungerford Court, 12/1, Hungerford Street, Calcutta) Indian Geotechnical Society, New Delhi Central Soil & Materials Research Station, New Delhi

Irrigation Department, Government of Uttar Pradesh, Roorkee Asia Foundations and Construction (P) Ltd, Bombay

University of Roorkee, Roorkee; and Institute of Engineers (India), Calcutta Cemindia Company Limited, Bombay

ittea, Boilibity

(Continued on page 2)

Copyright 1984

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 2720 (Part 1) - 1983

(Continued from page 1)

Members

SHRI M. IYENGAR

SHRI ASHOK K. JAIN

SHRI VIJAY K. JAIN (Alternate) JOINT DIRECTOR RESEARCH (GE)-I, Ministry of Railways

RDSO

TOINT DIRECTOR RESEARCH (GE)-II RDSO (Alternate)

LT-COL V. K. KANITKAR SHRI O. P. MALHOTRA

SHRI D. R. NARAHARI

SHRI V. S. AGARWAL (Alternate) SHRI T. K. NATRAJAN

SHRI RANJIT SINGH

SHRI P. D. DESHPANDE (Alternate)

DR G. B. RAO DR K. K. GUPTA (Alternate)

RESEARCH OFFICER (B& RRL)

SECRETARY DEPUTY SECRETARY (Alternate) Shri N. Sivaguru

SHRI P. R. KALRA (Alternate) SHRI K. S. SRINIVASAN

SHRI SUNIL BERRY (Alternate) DR N. Som

SHRI N. SUBRAMANYAM

ENGINEER SUPERINTENDING (P&DC)

EXECUTIVE ENGINEER (SMRD) (Alternate)

SHRI H. C. VERMA

SHRI H. K. GUHA (Alternate) SHRI G. RAMAN,

Director (Civ Engg)

Representing

Engineers India Limited, New Delhi G. S. Jain and Associates, Roorkee

Engineer-in-Chief's Branch, Army Headquarters Public Works Department, Chandigarh Administration, Chandigarh

Central Building Research Institute (CSIR),

Central Road Research Institute (CSIR), New

Ministry of Defence (R & D)

Indian Institute of Technology, New Delhi

Public Works Department, Government of Punjab. Chandigarh

Central Board of Irrigation and Power, New Delhi

Roads Wing (Ministry of Shipping and Transport)

National Buildings Organization, New Delhi

Jadavpur University, Calcutta

Karnataka Engineering Research Station. Krishnarajasagar

Public Works Department, Government of Tamil Nadu, Madras

All India Instrument Manufacturers and Dealers Association, Bombay

Director General, ISI (Ex-officio Member)

Secretary SHRI K. M. MATHUR Senior Deputy Director (Civ Engg), ISI

Soil Testing Procedures Subcommittee, BDC 23:3

Convener

DR ALAM SINGH

University of Jodhpur, Jodhpur

Members

SHRI AMAR SINGH

Central Building Research Institute (CSIR), Roorkee

SHRI M. R. SONEJA (Alternate)

(Continued on page 10)

Indian Standard

METHODS OF TEST FOR SOILS

PART 1 PREPARATION OF DRY SOIL SAMPLES FOR VARIOUS TESTS

(Second Revision)

0. FOREWORD

- **0.1** This Indian Standard (Second Revision) was adopted by the Indian Standards Institution on 28 November 1983, after the draft finalized by the Soil Engineering and Rock Mechanics Sectional Committee had been approved by the Civil Engineering Division Council.
- **0.2** With a view to establishing uniform procedure for the determination of different characteristics of soils, Indian Standards on methods of test for soils (IS: 2720) have been formulated in various parts. This part covers method of preparation of samples for the various laboratory tests covered in the standard. This part was first published in 1966 and revised in 1972. Since then more parts of this standard have been published covering additional characteristics besides some of the published parts have been revised wherein requirements have been modified. This revised version has therefore been formulated in order to up date in this respect.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard (Part 1) covers the method of preparation of dry samples from the bulk soil sample received from the field for various laboratory tests.

^{*}Rules for rounding off numerical values (revised).

2. APPARATUS

- 2.1 Wooden-Mallet for breaking soil clods.
- 2.2 Trays for air drying of soil, of suitable size and of non-rusting material.
- 2.3 Pulverizing Apparatus Either mortar and rubber covered pestle or a mechanical device consisting of mortar and a power-driven rubber covered pestle suitable for breaking up the aggregation of soil particles without reducing the size of the individual grains. Pestle and mortar made of soft wood may also be used.
- 2.4 Sampler A suitable riffle sampler or sample splitter for quartering the samples (see IS: 1607-1960*).
- 2.5 Sieves of sizes 75-mm, 63-mm, 37.5-mm, 19-mm, 13.2-mm, 9.50-mm, 6.7-mm, 4.75-mm, 2.00-mm and 425-micron [see IS: 460 (Part 1)-1978†].

2.6 Drying Apparatus

- a) Drying Oven Thermostatically controlled, with interior of non-corroding material to maintain the temperature between 105 and 110°C.
- b) Other suitable drying apparatus.

2.7 Balances

- a) Capacity 10 kg and minimum sensitivity 100 g.
- b) Capacity 1 kg and minimum sensitivity 1 g.
- c) Capacity 250 g and minimum sensitivity 0.01 g.

3. PREPARATION OF SAMPLE FOR TESTS

3.1 General — Soil sample as received from the field shall be dried in the air or in sun. In wet weather a drying apparatus may be used in which case the temperature of the sample should not exceed 60°C. The clods may be broken with a wooden-mallet to hasten drying. The organic matter, like tree roots and pieces of bark should be removed from the sample. Similarly, matter other than soil, like shells should also be separated from the main soil mass. A noting shall be made of such removals and their percentage of the total soil sample noted. When

^{*}Methods for dry sieving.

[†]Specification for test sieves: Part I Wire cloth test sieves (second revision). 400

samples are to be taken for estimation of organic content, lime content, etc, total sample should be taken for estimation without removing shells, roots, etc.

3.2 Drying of the Sample — The amount of drying depends upon the proposed test to be conducted on the particular sample. The type, temperature and duration of drying of soil samples for different tests are given in Table 1. When oven is used for drying, the temperature in the oven shall not exceed 110°C (see Note). Chemical drying of samples should not be adopted for any tests.

Note — Soils containing organic or calcareous matter should not be dried at temperature above 60°C .

TABLE 1 QUANTITY OF SOIL SAMPLE REQUIRED FOR CONDUCTING THE TESTS

(Clauses 3.2, 3.3 and 4.1)

St No.	Test	Type, Tempe- RATURE AND DUBATION OF DRYING	AMOUNT OF SOIL SAMPLE REQUIRED FOR TEST	DEGREE OF PUL- VERIZATION (PASSING IS SIEVE SIZE)	REF TO PART OF IS: 27201
(1)	(2)	(3)	(4)	(5)	(6)
i)	Water content	Oven, 24 h	As given in Table 2	_	Part 22
ii)	Specific gra- vity	Oven 105-110°C, 24 h	50 g for fine grained soils	2 mm	Part 3/Sec13
			400 g for fine, medium and coarse grained soils	_	Part 3/Sec 24
-iii)	Grained size analysis	Air drying	As given in Table 3	_	Part 45
iv.)	Liquid limit	\mathbf{do}	270 g	425 micron	Part 56
v)	Plastic limit	do	60 g	do	do

¹Methods of test for soils.

(Continued)

Determination of water content.

⁸Determination of specific gravity, Section 1 Fine grained soils.

Determination of specific gravity, Section 2 Fine, medium and coarse grained soils.

⁵Grain size analysis.

Determination of liquid and plastic limits.

TABLE 1 QUANTITY OF SOIL SAMPLE REQUIRED FOR CONDUCTING THE TESTS — Contd

SL No.	Test	TYPE, TEMPERATURE AND DURATION OF DRYING	AMOUNT OF SOIL SAMPLE REQUIRED FOR TEST	DEGREE OF PUL- VERIZATION (PASSING IS SIEVE SIZE)	REF TO PART OF IS: 27201
(1)	(2)	(3)	(4)	(5)	(6)
vi)	Shrinkage factors	Air drying	100 g	425 micron	Part 62
vii)	Compaction a) Light compaction	do	6 kg (15 kg if soil is susceptible to crushing)	19 mm	Part 78
	b) Heavy compaction	do	do	19 mm	Part 84
	c) Constant	do	2 kg	4·75 mm	Part 9 ⁵
viii)	Unconfined compressive strength	oven 110°C ± 5°C	1 k g	_	Part 10 ⁶
ix)	Triaxial com- pression (un- consolidated)		1 kg/5 kg	-	Part 117
x)	Triaxial compression (consolidated	do)	do	_	Part 128
xi)	Direct shear	Air drying/Oven 110°C±5°C	l kg	4·75 mm	Part 139

¹Methods of test for soils.

(Continued)

²Determination of shrinkage factors.

³Determination of water content dry density relation using light compaction.

⁴Determination of water content dry density relation using heavy compaction.

⁵Determination of dry density — moisture content relation by constant weight of soil method.

Determination of unconfied compressive strength.

Determination of shear strengh parameters of specimen tested in unconsolidated undrained triaxial compression without the measurement of pore water pressure.

^{*}Determination of shear strength parameters of soil from consolidated undrained triaxial compression test with measurement of pore water pressure.

Direct shear test.

TABLE 1 QUANTITY OF SOIL SAMPLE REQUIRED FOR CONDUCTING THE TESTS - Contd

SL No.	Test	TYPE, TEMPE- RATURE AND DURATION OF DRYING	Amount of Soil Sample Required For Test	DEGREE OF PUL- VERIZATION (PASSING IS SEIVE SIZE)	REF TO PART OF IS: 27201
(1)	(2)	(3)	(4)	(5)	(6)
xii) I	Density index (relative density)	Oven, 105-110°C, 24 h	As per size of particle given below: 75 mm 45 kg 37.5 ,, 12 ,, 19 ,, 12 ,, 9.50 ,, 12 ,, 4.75 ,, 12 ,,		Part 143
xiii)	Consolidation properties	Air drying/Oven 110°C ± 5°C	500 g	_	Part 15 ³
xiv)	CBR	Air drying	6 kg	19 mm	Part 164
xv)	Permeability	Oven, 105-110°C, 24 h	2.5 kg (100 mm dia)/ 5 kg (200 mm dia)	9·5 mm	Part 17 ⁵
xvi)	Field moisture equivalent	Air drying	15 g	425 micron	Part 18 ⁶
xvii)	Centrifuge moisture equivalent	do	10 g	do	Part 19 ⁷
xviii)	Linear shrinkage	do	450 g	$d\mathbf{o}$	Part 208
xix)	Chemical tests				
	a) Total soluble solids	Oven, 105-110°C, 24 h	10 g	2 mm	Part 219
	b) Organic matter	Air drying	100 g	do	Part 2210

¹Methods of test for soils.

(Continued)

Determination of density index (relative density) of cohesionless soils.

³Determination of consolidation properties.

⁴Laboratory determination of CBR.

Laboratory determination of permeability.

Determination of field moisture equivalent,

Determination of centrifuge moisture equivalent.

⁸Determination of linear shrinkage,

Determination of total soluble solids.

¹⁰Determination of organic matter.

TABL	E 1 QUANTIT	Y OF SOIL SA	MPLE REQ	UIRED FOR C	ONDUCTING
SL No.	Тевт	TYPE, TEMPE- RATURE AND DURATION OF DRYING	AMOUNT OF SOIL SAMPLE REQUIRED FOR TEST		REF TO PART OF IS: 27201
(1)	(2)	(3)	(4)	(5)	(6)
	c) Calcium carbonate	Oven, 105-110°C 24 h	, 5 g		Part 232
	d) Cation exchange capacity	do	80-130 g		Part 24°
	e) Silica-ses- quioxide ratio	d <i>o</i>	15 g		Part 254
	f) pH value	do	30 g	425 micron	Part 265
	g) Total soluble sulphates	do	30 g	_	Part 27 ⁸
xx)	Vane shear	Air drying/oven 110°C ± 5°C	250 g	. _	Part 307
xxi)	Negative pore water pressure	do	1 kg/5 kg		Part 358
xxii)	Permeability of granular soils	do	d o		Part 369
·xxiii)	Sand equivalent val	105 ± 5°C ue	1 500 g	4.75 mm	Part 3710
xxiv)	Direct shear	Air drying up	to 120 g	Above 4.75 mm	Part 39/Sec 111
xxv)	Free swell index	Oven dry	20 g	425 micron	Part 4012
xxvi)	Swelling pressure	Air drying/ Oven dry	2 kg	2 mm	Part 4113

¹Methods of test for soils.

²Determination of calcium carbonate.

^{*}Determination of cation exchange capacity.

⁴Determination of silica sesquioxide ratio.

Determination of pH value.

Determination of total soluble sulphates.

Laboratory vane shear test.

⁸Measurement of negative pore water pressure.

^{*}Laboratory determination of permeability of granular soils (constant head).

¹⁰Determination of sand equivalent values of soils and fine aggregates.

¹¹Direct shear test for soils containing gravel: Section 1 Laboratory test.

¹² Determination of free swell index of soils.

¹⁸ Measurement of swelling pressure of soils.

3.3 Degree of Pulverization — The big clods may be broken with the help of wooden mallet. Further pulverization may be done in pestle and mortar. The pulverized soil shall be passed through the specified sieve for the particular test and the soil retained on that sieve shall be again pulverized for sieving. This procedure should be repeated until on further attempts at pulverizing very little soil passes through the specified sieve. Care should be taken not to break up the individual soil particles (see Table 1).

4. QUANTITY OF SAMPLE

4.1 The quantities of soil sample required for conducting various laboratory tests are given in Table 1 for guidance.

Note - For actual quantities, corresponding part of IS: 2720 shall be referred.

4.2 When a smaller quantity has to be taken out of a bigger soil mass the representative sampling shall be done by quartering or riffling.

NOTE—In the case of coarse gravel or gravelly soils quartering by forming a cone shall not be done. The entire sample shall be thoroughly mixed and spread on a flat surface. The sample so spread shall be divided into four quadrants and diagonally opposite quadrants mixed. This process shall be repeated till the desired quantity of sample is obtained.

TABLE 2 QUANTITY OF SAMPLE REQUIRED FOR DETERMINATION OF WATER CONTENT

Size of Particles More Than 90 Percent Passing	Minimum Quantity of Soil Specimen to be Taken for the Test Mass in g	
425-micron IS Sieve	25	
2-mm IS Sieve	50	
4.75 mm IS Sieve	200	
9.50 mm IS Sieve	300	
19 mm IS Sieve	5 0 0	
37.5 mm IS Sieve	1 000	

TABLE 3 QUANTITY OF SOIL REQUIRED FOR GRAIN SIZE ANALYSIS

MAXIMUM SIZE OF MATERIAL PRESENT IN SUBSTANTIAL QUANTITIES mm	Mass to be Taken for Test kg	
75	60	
37.5	25	
19	6.5	
13 2	3.5	
9.5	1.5	
6.7	0.75	
4.75	0.4	

IS: 2720 (Part 1) - 1983

(Continued from page 2)

Representing	
Irrigation Department, Government of Punjab, Chandigarh	
Irrigation Department, Government of Uttar Pradesh, Lucknow	
Ministry of Railways	
Central Soil and Materials Research Station, New Delhi	
Geologist Syndicate Private Limited, Calcutta	
University of Roorkee, Roorkee	
Indian Institute of Technology, New Delhi	
Central Road Research Institute (CSIR), New Delhi	
Engineer-in-Chief's Branch, Army Headquarters	
Associated Instruments Manufacturers (I) Private Limited, New Delhi	

PROP T. S. NAGARAJ (Alternate)