

<b>Technical Specifications</b>	
<b>Model</b>	MatView-AC415V-15KW-RLC AC Load Bank
<b>Load Element</b>	Resistor, inductor and capacitor
<b>Load Voltage</b>	AC-415V three phase four wire
<b>Frequency</b>	50Hz
<b>3 Phase Load Power</b>	R=15KW, L=15KVar, C=15KVar
<b>Load Steps</b>	Resistive load steps: 1W- 2kW
<b>Per Phase</b>	Inductive load steps: 1Var - 2kVar Capacitive load steps: 1Var - 2kVar
<b>Power Factor</b>	Leading and lagging power factor 0-1.0 adjustable
<b>Digital Meter</b>	voltage, current, active power, reactive power, apparent power, power factor, energy, frequency
<b>Auxiliary Supply</b>	230V 50Hz, single phase
<b>Control Modes</b>	Touch Display / Rs-485(for external Control)
<b>Insulation Class</b>	F
<b>Cooling Mode</b>	Force-air vertical cooling, by axial-flow fans.
<b>Work Mode</b>	Continuous work
<b>Protections</b>	Overheating/Buzzer alarm, Overheating/Over current, over voltage, over load protection, emergency stop button.
<b>Ambient Temperature</b>	-10°C ~ +60°C
<b>Mobility</b>	Four wheels
<b>Humidity</b>	≤95%