

KCV-P SERIES -CHECK VALVE PRESSURE SEAL



Valve size	2" to 24"
Design Standard	API & Non API / BS
Pressure Rating	Upto 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld

KFB SERIES BALL VALVE FLOATING TWO PIECE/THREE PIECE

Valve size	1/4" to 8"
Design Standard	API & Non API
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld



KTM SERIES BALL VALVE TRUNNION MOUNTED TWO PIECE/THREE PIECE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld

KCV-B SERIES CHECK VALVE BOLTED BONNET



Valve size	2" to 24"
Design Standard	API & Non API / BS
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld

KGV SERIES GATE VALVE PRESSURE SEAL

Valve size	2" to 24"
Design Standard	API & Non API / BS
Pressure Rating	900# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld



KGLV -P SERIES GLOBE VALVE PRESSURE SEAL



Valve size	2" to 16"
Design Standard	API & Non API / BS
Pressure Rating	900# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld

KBF-C SERIES CONCENTRIC BUTTERFLY VALVE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# & 300#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange Type / Wafer Type / Lug Type

KBF-T SERIES TRIPLE OFFSET BUTTERFLY VALVE

Valve size	3" to 24"
Design Standard	API & Non API
Pressure Rating	150# till 1500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange Type / Wafer Type / Lug Type



KBF-D SERIES DOUBLE OFFSET BUTTERFLY VALVE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# & 600#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange Type / Wafer Type / Lug Type

KCV-S SERIES -SINGLE PLATE CHECK VALVE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# & 300#
Material	Cast / Alloy / Stainless Steel
End Connection	Wafer Type

KCV-D SERIES DUAL PLATE CHECK VALVE

Valve size	3" to 24"
Design Standard	API & Non API
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange Type



KCV-D SERIES DUAL PLATE CHECK VALVE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# & 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Lug Type

KCV-D SERIES DUALPLATE CHECK VALVE



Valve size	2" to 24"
Design Standard	API & Non API
Pressure Rating	150# & 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Wafer Type

KQE SERIES QUICK EXHAUST VALVE

Medium	Compressed Air, Filtered, lubricated and non-lubricated
Design	Diaphragm operated valve
Operating Term	+ 20°C to +80°C
Operating Pressure	0.5 - 10 bar
Material	Alluminium Alloy (Anodized) Body & Cover, Nitrile seals, Brass, SS304, SS316
Sizes	1/4", 3/8", 1/2", 3/4" & 1" BSP(F) or NPT F



KFC SERIES FLOW CONTROL VALVE



Medium	Water, Gas , Air
Design	Needle operated Valve
Operating Term	-10°C to +70°C
Operating Pressure	1-10 bar
Material	SS304, SS316 and Aluminium, Nitrile seals
Sizes	1/4", 3/8", 1/2", 3/4" & 1" BSP(F) or NPT F

KFB SERIES BALL VALVE FORGED STEEL THREE PIECE



Valve size	1/4" to 2"
Design Standard	API & Non API
Pressure Rating	150# & 800#
Material	Forged / Alloy / Stainless Steel
End Connection	Threaded (NPT / BSP) / Socket / Butt Weld

KGV-F & KGV-B SERIES GATE VALVE BOLTED BONNET

Valve size	1/4" to 24"
Design Standard	API & Non API
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld



KGLV-BL SERIES GLOBE VALVE BOLTED BONNET



Valve size	1/4" to 16"
Design Standard	API & Non API / BS
Pressure Rating	150# till 2500#
Material	Cast / Alloy / Stainless Steel
End Connection	Flange (FF, FE & RTJ) / Butt Weld

KRP AND KSY SERIES PNEUMATIC ACTUATORS

	Medium	Gas ,Water, any liquids per valve specification
	Design	Diaphragm operated ,Electrically Operated, Rack and Pinion and Scotch Yoke
	Operating Term	-60°C to +120°C
	Operating Pressure	3 TO 10 BAR
	Material	Hard anodized Aluminum/Cast Steel / Stainless Steel
	Sizes	4 NM TO 1,50000 NM
	Standards	Actuator to Valve Mounting ISO 5211 Actuator to Solenoid and Accessories Mounting Namur VDI/VDE3845 External Corrosion Protection in compliance with ISO 12944-2 and EN15714-3 Class C3

VALVE AUTOMATION SYSTEM

Valve size	1/2" to 32"
Design Standard	API & Non API
Pressure Rating	150# & 2500#
End Connection	Flange Type
Material	Cast / Alloy / Stainless Steel/ Accessories as per customer specifications
Sizes	5 NM TO 150000 NM as per customer specification



KPREVA SERIES PRESSURE REGULATING/RELIEF VALVE



Function	Reducing / Relief/ Back pressure/Deluge valve
Seat Variation	Single / Double
End Connections	Flanged/ Threaded
Inlet/Outlet Diameter	From 1/2" up to 20"
Max rating	ANSI 150 to ANSI 1500
Temperature min/max	-10 to + 540 °C
CV Min/Max	0,04 / 1460
Set point min/max	0,5 / 46 barg
Construction Material	
Body	Carbon & Stainless Steel, Cast Iron
Spring case	Carbon & SS
Hydraulic loop	Copper + brass, 316 SS
Diaphragm	Polychloroprene / NBR / PTFE / Reinforced EPDM/ Nylon Reinforced Buna - N

This information is for reference purpose. For more detail information please contact factory