

OPTIONS**Flush Volume**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

Finish

Brushed Stainless (SF)

Matte Black (MB)

Matte White (MW)

Polished Chrome (CP)

Water Efficiency

High Efficiency

Low Consumption

Compliances & Certifications

ADA Compliant

BREEAM Water Credit

Green Globes Water Credit

cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001)

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard TRF 8156 shown

DESCRIPTION

TruFlush Concealed Sensor Water Closet Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Battery powered infrared sensor provides hands free activation
- Vandal-resistant wall plate with electronic override button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [TruFlush](#)
- ▶ [TruFlush Installation](#)
- ▶ [TruFlush Maintenance](#)
- ▶ [TruFlush Flush Line](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com