

**OPTIONS**

**Flush Volume**

0.25 gpf (0.9 Lpf) (0.25)

0.5 gpf (1.9 Lpf) (0.5)

**Finish**

Brushed Stainless (SF)

Matte Black (MB)

Matte White (MW)

Polished Chrome (CP)

**Power Type**

Battery

**Activation**

Sensor

**Valve**

Piston

**Water Efficiency**

High Efficiency

**Fixture Type**

Urinal

**Fixture Connection**

Top Spud

**Installation**

Concealed

**Override**

Electrical (OR)

**Compliances & Certifications**

ADA Compliant

BREEAM Water Credit

Green Globes Water Credit

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard TRF 8196 shown

**DESCRIPTION**

TruFlush Concealed Sensor Urinal Flushometer

**FEATURES**

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Battery powered infrared sensor provides hands free activation
- Vandal-resistant wall plate with electronic override button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

**DOWNLOADS**

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Additional Downloads](#)

**VIDEOS**

- ▶ [TruFlush](#)
- ▶ [TruFlush Installation](#)
- ▶ [TruFlush Maintenance](#)
- ▶ [TruFlush Flush Line](#)