



Email: sales@greyflow.net.au

sammilani@awws.com.au

# FILTERSORB®

REVOLUTIONARY SCALE PREVENTION MEDIA

#### **ADVANTAGES**

- No salt required
- No backwashing required
- No regeneration cycle required
- No increase in sodium contentin water
- Removes the previous scales of plumbing
- Catalytic process converts Ca and Mg into harmless micro crystals
- Maintenance free. No extra cost incurred.
- No chemicals required for disinfection
- No electrical connections required
- No drain connections required
- No control valves required
- Very easy to install
- Great savings against convetional salt based water softeners
- Provide the best quality healthy water without the addition of Sodium or Phosphates







#### **GREEN TECHNOLOGY!**









### **FEATURES**

5 - 7 years media life

**Best Quality Drinking Water** 

Nucleation Assisted Crystallization (NAC)







Email: sales@greyflow.net.au sammilani@awws.com.au



#### WHAT IS FILTERSORB® SP3?

worldwide since 2005.

Watch®'s core motivation for developing this product was to Glass grains crystallization sites provide increased find an alternative to conventional ion exchange based water softeners, reverse osmosis or other chemical based systems that prevent scale.

Recent restrictions placed upon the above mentioned technology lead to an environment friendly, cost effective FILTERSORB®SP3 completely takes care of the primary cause of scale forming cations viz. Ca2+ and Mg2+.

#### **WORKING PRINCIPLE**

When the hard water under goes nucleation in the pressure vessel, the calcium bicarbonate Ca(HCO<sub>3</sub>)<sub>2</sub> is transformed into aragonite form of calcium carbonate CaCO<sub>3</sub> crystals. These crystals are formed through decomposition and crystallization process, forming very stable harmless crystals.

The following equation describes the reaction that occurs inside the pressure vessel when flow over grains of nucleatio

 $Ca(HCO_3)_2 \rightarrow CaCO_3 + CO_2 + H_2O_3$ (Micro-Crystals) (Colloid) (Pure)

The name fragment "SP (Scale Prevention) 3" is to indicate this unique transformation of water hardness Ca(HCO<sub>2</sub>)<sub>2</sub> into 3 components viz.

- 1. CaCO<sub>3</sub> (micro-crystals)
- 2. CO<sub>2</sub>(colloid) and
- 3. H<sub>2</sub>O(pure)

In the pressure vessel, the equilibrium of carbonate species in water is changed, assisted by the driving force of stable crystal formation and therefore the reaction is pushed to the right -. With this technology, as long as CO<sub>2</sub> is being removed the soluble Ca(HCO<sub>3</sub>)<sub>2</sub> converts into insoluble calcium carbonate (CaCO<sub>3</sub>) crystals

FILTERSORB®SP3 is the result of extensive research work The calcium carbonate crystals grow steadily. They are very along with its undisputable success in the market, stable and cannot dissolve (incapable of forming scale) in the water.

> nucleation sites for the formation of submicron sized CaCO<sub>2</sub> crystals. Hence this amazing process is called NUCLEATION ASSISTED CRYSTALLIZATION or NAC in short.

#### **ADVANTAGES & FEATURES**



## SALT-FREE SCALE PREVENTION











Email: sales@greyflow.net.au sammilani@awws.com.au

#### PHYSICAL CHARACTERISTICS

Appearance		White / opaque solid granules
Composition		modified ceramic beads
Bulk density	SI US	780 kg/m³ 48.7 lb / ft³
Particle size	SI	0.55 - 0.75 mm
Mesh size	US	20 x 35
Moisture content		10 - 25 %

#### **OPERATIONAL PARAMETERS & WATER IMPURITIES**

Flow direction		Up Flow
Recommended	SI	5 – 80 °C
operating time	US	41 – 176 °F
ph range		6.5 - 9.5
Hardness, max.	SI	1338 ppm (mg/l)
	US	75 gpg
Salinity, max.		35000 ppm (mg/l)
Iron, max.		0.5 ppm (mg/l)*
Manganese, max.		0.05 ppm (mg/l)
Free chlorine, max.		3 ppm (mg/l)
Copper, max.		1.3 ppm (mg/l)
Oil		free
Hydrogen sulfide		free

\*FILTERSORB®SP3 is able to remove Iron from water with very high efficiency.

**Note:** Do not use where water is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the unit. System must be maintained according to manufacturer's instructions. Pre-treatment for sediment, Iron, Hydrogen Sulfide, Manganese, hydrocarbons and Copper may be required depending on conditions. Install systems in new facilities with copper pipe after six weeks of water use.

#### **APPLICATIONS**

FILTERSORB®SP3 has proven itself in a variety of applications as an alternative to ion exchange softening or other conventional water treatment methods. The maintenance-free characteristics make it especially suited for Foodservice and Commercial applications where equipment maintenance is often overlooked. FILTERSORB® SP3 treated water preserves the essential minerals Calcium and Magnesium, making the water most healthiest drink available.

Home Appliances: Faucets, water pipes, shower heads, shower cabins, toilets. All beverage systems, kitchen machines, dish washers, ice cubes, compact washers and dryers.

*Major appliances*: Central heating, air conditioners, water heaters, air humidifiers, coffee and tea makers, solar heating systems, water coolers.

**Boilers:** Hot water boilers, central heating boilers, combo boilers, catering water boilers, boilers and pool heaters, commercial water heaters, industrial hot water boilers.

**Cooling towers:** Closed circuit cooling towers, open circuit cooling towers, concrete cooling towers, cross flow cooling towers.

Industrial appliances: Winery, Car Washing, Diary Processing, Food & Beverages, Injection Moulding, Irrigation, Nurseries, Reverse Osmosis pre-treatment etc.

#### **OTHER APPLICATIONS**

- Irrigation
- Swimming pools and SPA
- Dairy Processing
- Winery and Beverages
- Planting and Gardening
- Automobile Washing
- Hotel, Restaurants and Institutions
- Coffee and Tea-machines
- Vending appliances and many more...

BEST SUITABLE FOR









Email: sales@greyflow.net.au sammilani@awws.com.au



# WHY WE CONSIDER FILTERSORB®SP3 TO BE THE BEST?

- ✓ No TDS change: As FILTERSORB®SP3 does not remove or add anything to the water. As no ion-exchange chemistry is used,the TDS of the water remains unchanged before and after the treatment.
- No pH change: pH value of the water remains the same. This factor makes the treated water suitable for almost any use where corrosion is concerned
- ✓ **Biocidal effect:** The NAC process creates the conditions that water dissolved CO<sub>2</sub> agglomerate to form micro-bubbles. These CO bubbles actively destroy bacterial membranes acting as a biocide. So along with the scale prevention **FILTERSORB®SP3** also helps to prevent Biofouling.

#### **CERTIFICATIONS**

#### FILTERSORB®SP3

Certified under ANSI/NSF 61 from WQA, USA Tested to meet MSZ 448-36:1985 standard (Hungary). Certified from Department of Environmental Hygiene (Poland).

Tested to meet WRAS (Water Regulations Advisory Scheme, British Standard, UK) Standard of Product Quality and High temperature

- Minerals Preserved: FILTERSOR® SP3 does not add sodium or any chemicals to the water. It simply preserves the Calcium and Magnesium contents of water, making the treated water arguably the healthiest mineral water available. Both Calcium and Magnesium are quintessential for nervous systems and muscles functionalities. They are indispensable parts in the cell chemistry of the plants and most of the life forms on earth.
- ✓ De-Scaling: Not only does FILTERSORB®SP3 prevent scale formation, but it also helps to remove the previously formed scales. During the flow some of the micro-bubbles are losing a small amount of CO₂, which diffuses rapidly in water and interact with surface scale, especially in closed spaces (pipes, boilers, etc). As a result, the scale which is already present on these surfaces is removed slowly.

**Special Information:** FILTERSORB® SP3 has good capacity to absorb Iron, Copper, Manganese, Lead, Zinc etc. Hence in high concentration presence of these contaminants the FILTERSORB® SP3 beads may change color and come to an end of the media life. From studies it's also possible that the media might change color due to dye leaching from the container tank made of polyethylene.

In case of any strange color change of the FILTERSORB® SP3 media beads or the treated water is noticed, please contact us with detailed water analysis.

Disclaimer: The information in this publication is based on reliable data and is provided in good faith, without warranty or performance guarantee, as product use conditions are beyond our control. Watch Water GmbH, Germany, does not offer express or implied warranties, including merchantability or fitness for a specific purpose. Users should assess product suitability and performance with their equipment. Specifications may change without notice. Please note that the filter media in this brochure do not eliminate bacteria. Do not use our products with microbiologically unsafe or unknown-quality water without proper disinfection. Watch Water GmbH. Germany, is not liable for consequential or incidental damages, such as lost profits from product use.



#### **Standard Packaging**

Packging Weight of product

49 kg

Quantity/ pallet

18

Gross Wt./ pallet

965 kg

Certification NSF/ANSI/ CAN 61 & 372

★ Other packaging can be considered on request



Australian national Distributor Unit 6, 18 Buckingham drive, Wangara, WA 6065 Tel: +61405459533

Email: sales@greyflow.net.au sammilani@awws.com.au