

Nayax

EV Meter Pay2



Electrical Data

- AC Power Supply
- AC Input Voltage
- AC Output Voltage
- Maximum Input / Output Current
- Maximum Input / Output Power
- Number of Plugs
- 3P + N + PE
- 380-400 VAC +/-10%, 50-60Hz
- 380-400 VAC +/-10%, 50-60Hz
- 2*3x32A
- 2*22kW
- Two

Communication

- Interface Protocol Wireless Connection
- OCPP 1.6 Supported 4G

Safety & Protections

- Safety Protections
- Power Limit Control
- Type 2 Socket Protection
- Available Connections
- Electronic RCD 30mA AC & Electronic 6mA DC & Fault current detection
- Mode 3 PWM control according to IEC 61851-1
- IEC 62196-1 , IEC 62196-2
- Type 2 Socket or 5m Cable with Plug

Enclosure & Environmental Conditions

- IP Rating
- Enclosure Material
- Operating Temperature
- Ambient Temperature Storage
- Status LEDs
- Light Beacon
- Built-in Energy Meter
- IP55
- PC + UV
- (-25°C) to (+55°C)
- (-30°C) to (+70°C)
- Yes
- RGB colour indicator
- Yes

Weight & Dimensions (W×H×D)

- Cable
- Socket
- 450x300x180 mm, 8Kg
- 480x300x180 mm, 6Kg

Optional Devices

- Type 2 Socket Protection
- Dynamic Load Management
- Pedestal
- Shutter
- Yes
- Yes